

Hondzyk.com international Click Tag categorization, ver 20140103

ClickTag ID	ClickTag Code	Description	Country of Origin
1	<p>ClickTAG parameter code for ActionScript 2:</p> <pre>on (release) { if (clickTAG.substr(0,5) == "http:") { getUrl(clickTAG, "_blank"); } }</pre> <p>ClickTAG parameter code for ActionScript 3:</p> <pre>import flash.events.MouseEvent; import flash.net.URLRequest; // someButton_or_displayObject_to_receive_mouseClick.addEventListener(MouseEvent.CLICK, function(event: MouseEvent) : void { flash.net.navigateToURL(new URLRequest(root.loaderInfo.parameters.clickTAG), "_blank"); });</pre> <p>Replace someButton_or_displayObject_to_receive_mouseClick with the actual name of button that will receive the click.</p>	<p>Google AdWords AS2 and AS3 script definition.</p>	Worldwide
2	<pre>on (release) { if (_root.clickthru == undefined && _root.clickTag) { _root.clickthru = _root.clickTag; } if (_root.clickthru == undefined && _root.clickTAG) { _root.clickthru = _root.clickTAG; } if (_root.clickTarget == undefined) { _root.clickTarget = "_top"; } } getUrl(_root.clickthru, _root.clickTarget); }</pre>	<p>AS2 script approved by CZ authority called SPIR. Reads all "clickthru", "clickTag" or "clickTAG" for target URL and may understand to "clickTarget" value for target window definition.</p>	CZ
3	<pre>on (release) { if (_root.clickthru == undefined && _root.clickTag) { _root.clickthru = _root.clickTag; } if (_root.clickthru == undefined && _root.clickTAG) { _root.clickthru = _root.clickTAG; } if (_root.clickTarget == undefined) { _root.clickTarget = "_top"; } } getUrl(_root.clickthru, _root.clickTarget); }</pre>	<p>AS2 script by CZ supplier Seznam.cz</p>	CZ
4	<pre>on (release) { getUrl(_root.clickTAG, "_blank"); }</pre>	<p>clickTAG to blank</p>	LV
5	<pre>on (release){ getUrl("javascript:"+_root.onCrossClick+"()", "_self"); }</pre>	<p>CrossClick</p>	LV
6	<pre>on (release){ getUrl(_root.clickTAG, _root.target); flash.external.ExternalInterface.call("smartad_click", _root.id); }</pre>	<p>smartad</p>	LV
7	<pre>on(release){ getUrl(_root.clickTag, "_blank"); }</pre>	<p>clickTag to blank</p>	LV
8	<pre>on (release) { getUrl(clicktag, "_blank"); }</pre>	<p>clicktag to blank</p>	LV